



IBM 4232-302	SerialParallel	600 cps Fast Draft mode 400 cps DP Mode 200 cps Text Mode 100 cps NLQ Mode
Print Options	Vertical Spacing	6 or 8 lines per inch, selectable from operator panel 3,4 ,6 or 8 lines per inch, as selected by host
	Horizontal Spacing	10, 12, 15, 16.7, 17.1, 20 characters per inch
Paper Specifications	Features	Continuous form width: 3" to 15" Continuous form length: 3" to 14" Cut Sheet length: 5" to 14" Cut Sheet width: 3" to 14" One- to six-part forms
Printer Emulations		Epson FX 1050; IBM Proprinter® III XL; 4224 3xxi
Systems Attachments		AS/400 via ASCII Workstation Controller or PC -348x, 3477, 3197 Display StationRS/6000 Direct attach toSystem or WorkstationLAN via external Ethernet or token ring via PC 3System/390 : 3174 Controll ascii adapter, PC, 3482 display
Misc. Features	Power Requirements	100/127, 50/60 Hz
	Power Consumption	120VAC -90 watts maximum 220VAC -90 watts maximum
	Noise Levels	53 dBA
Dimensions(H X W X D)	Unit	W 25.9" x D 15.6" x H 12.4"
Weight	Unit	45 lbs.